




















STANDARDPINMAP CONNECTORS

Funktion	Farbe (kann bei einigen Kabelltypen ab- weichen)	Sanube S1 16p.	15p. ISO 12098 (24V)	15p. HDSCS	13p. ISO 12098 (24V)	13p. ISO 11446 (12V)	Sanube 8p.	7p. ISO 1185	7p. ISO 3731	7p. DIN Bajonett (AMP)	7p. 12V ISO 1724	Sanube 5p. Bajonett	Sanube S1 4p.	Superseal 2p.	Super-seal 4p.	Deutsch 2p.	Deutsch 4p.	Deutsch 6p.	Deutsch 8p.		
Blinker links	GELB	A	1	7	3	1	1	3	-	4	1	BL	1	-	4	-	1	1	1		
Blinker rechts	GRÜN	B	2	8	5	4	4	5	-	4	4	BL	1	-	4	-	1	4	4		
Nebelleuchte	BLAU	C	3	1	9	2	2	-	7	6	(2)	S	-	-	-	-	-	(2)	2		
Masse	WEISS	D	4	2	1	3	3	1	-	1	3	31	3	1	1	1	4	3	3		
Standlicht links	SCHWARZ	E	5	3	2	7	7	2	-	2	7	UR	2	2*	3	2*	3	7	7		
Standlicht rechts	BRAUN	F	6	4	6	5	5	6	-	2	5	UR	2	2*	3	2*	3	5	5		
Bremse	ROT	G	7	5	4	6	6	4	-	5	6	BR	4	-	2	-	2	6	6		
Rückfahrer	GRAU	H	8	6	8	8	8	-	3	3	-	S	-	-	-	-	-	(2)	8		
Allgem.Stromvers.	BRAUN/BLAU	I	9	9	10	9	-	-	4	-	-	-	-	-	-	-	-	-	-		
Verschleißanzeige	BRAUN/ROT	J	10	10	-	10	-	-	-	-	-	-	-	-	-	-	-	-	-		
Federspeiche	GELB/SCHWARZ	K	11	11	7	-	-	7	-	-	-	-	-	-	-	-	-	-	-		
Achslift	ROSA	L	12	12	13	-	-	-	6	-	-	-	-	-	-	-	-	-	-		
Masse f. Elektronik	WEISS/SCHWARZ	M	13	13	-	13	-	-	1	-	-	-	-	-	-	-	-	-	-		
Datenleitung	VIOLETT	N	14	14	11	-	-	-	2	-	-	-	-	-	-	-	-	-	-		
Datenleitung	ORANGE	O	15	15	12	-	-	-	5	-	-	-	-	-	-	-	-	-	-		
CAN H		P	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
CAN L		R	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
																					

Y: Marketing: Standardpinmap Conn. D